



AM 125EE SERIES

MAKING WATER SOFT FOR OVER 40 YEARS

THE AUTOMATIC WATER CONDITIONER THAT GIVES YOU MORE!

AM 125EE DUPLEX SERIES



- 1 ¼" Control – Ideal for large residential/light commercial applications requiring up to 35 GPM
- Three modes of operation: meter immediate, meter delayed or time clock delayed
- Solid state microprocessor with easy access front panel settings
- Front panel display for time of day, volume remaining, current flow rate and total volume used (totalizer)
- Multiple programming options, powerful, reliable and user-friendly electronics automatically monitor water-treatment functions including:
 - Days since last regeneration
 - Gallons since last regeneration
 - Number of days in service since start up
 - Total number of regenerations
- Optional double backwash feature offers optimum regeneration, cleaning ability and efficiency
- Fully adjustable cycle times with 6-cycle control delivers controlled backwash, downflow bringing/slow rinse, second backwash, fast rinse, refill and downflow service
- Coin Cell Lithium battery back-up with an 8 hour carry over

Models	AM 125-EE 48	AM 125-EE 60	AM 125-EE 75	AM 125-EE 90	AM 125-EE 120	AM 125-EE 150
Exchange Capacity Per Tank Grain @ lb. Salt	Min. 30,000 @ 9	Min. 40,000 @ 12	Min. 50,000 @ 15	Min. 60,000 @ 18	Min. 80,000 @ 24	Min. 100,000 @ 30
	Med. 36,000 @ 13.5	Med. 48,000 @ 16	Med. 60,000 @ 20	Med. 72,000 @ 24	Med. 96,000 @ 32	Med. 120,000 @ 40
	Max. 45,000 @ 22.5	Max. 60,000 @ 30	Max. 75,000 @ 38	Max. 90,000 @ 45	Max. 120,000 @ 60	Max. 150,000 @ 75
Resin (Cu Ft)	1.5	2.0	2.5	3.0	4.0	5.0
Mineral Tank Size (inches)	10 x 54	12 x 52	13 x 54	14 x 65	16 x 65	18 x 65
Brine Tank Size (in.) Salt Storage (lbs.)	18 x 33 300	18 x 40 450	18 x 40 450	24 x 41 550	24 x 41 550	24 x 50 550
Pipe Size (inches)	1¼	1¼	1¼	1¼	1¼	1¼
Flow Rate (Cont. 15 psi) (Peak 25 psi)	19 28	23 31	24 32	24 33	25 34	27 35
Backwash Rate (gpm)	2.2	3.2	4.2	5.3	6.5	7.5

SOLD BY:

Products of



AM 125EE Plumbing / Wiring Diagram

