



AM 200 SERIES

MAKING WATER SOFT FOR OVER 40 YEARS

THE AUTOMATIC WATER CONDITIONER THAT GIVES YOU MORE!

AM 200 Series



- 2" Control - Ideal for commercial/industrial applications requiring up to 119 GPM
- Three modes of operation: meter immediate, meter delayed or time clock delayed
- Solid state microprocessor with easy access front panel settings
- Front panel display for time of day, volume remaining, current flow rate and total volume used (totalizer)
- Multiple programming options, powerful, reliable and user-friendly electronics automatically monitor water-treatment functions including:
 - Days since last regeneration
 - Gallons since last regeneration
 - Number of days in service since start up
 - Total number of regenerations
- Double backwash feature offers optimum regeneration, cleaning ability and efficiency
- Fully adjustable cycle times with 6-cycle control delivers controlled backwash, downflow brining/slow rinse, second backwash, fast rinse, treated water refill and downflow service
- Coin Cell Lithium battery back-up with an 8 hour carry over



Models	AM 200-60	AM 200-75	AM 200-90	AM 200-120	AM 200-150	AM 200-180	AM 200-210	AM 200-240	AM 200-300	AM 200-450	AM 200-600
Exchange Capacity Grain @ lb. Salt	Min. 40,000 @ 12	Min. 50,000 @ 15	Min. 60,000 @ 18	Min. 80,000 @ 24	Min. 100,000 @ 24	Min. 120,000 @ 36	Min. 140,000 @ 42	Min. 160,000 @ 48	Min. 200,000 @ 60	Min. 300,000 @ 60	Min. 400,000 @ 120
	Med. 48,000 @ 16	Med. 60,000 @ 20	Med. 72,000 @ 24	Med. 96,000 @ 32	Med. 120,000 @ 40	Med. 144,000 @ 48	Med. 168,000 @ 56	Med. 192,000 @ 64	Med. 240,000 @ 80	Med. 360,000 @ 120	Med. 480,000 @ 160
	Max. 60,000 @ 30	Max. 75,000 @ 38	Max. 90,000 @ 45	Max. 120,000 @ 60	Max. 150,000 @ 75	Max. 180,000 @ 90	Max. 210,000 @ 105	Max. 240,000 @ 120	Max. 300,000 @ 150	Max. 450,000 @ 60	Max. 600,000 @ 300
Resin (CU Ft) Per Tank	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	10.0	15.0	20.0
Mineral Tank Size	13" x 54"	13" x 54"	14" x 65"	16" x 65"	18" x 65"	21" x 62"	21" x 62"	24" x 72"	24" x 72"	30" x 72"	36" x 72"
Brine Tank Size Salt Storage	18" x 40" 450 lbs.	18" x 40" 450 lbs.	24" x 41" 550 lbs.	24" x 50" 700 lbs.	24" x 50" 700 lbs.	24" x 50" 700 lbs.	24" x 50" 700 lbs.	24" x 50" 700 lbs.	24" x 50" 700 lbs.	30" x 50" 1000 lbs.	39" x 48" 1200 lbs.
Pipe Size	2"	2"	2"	2"	2"	2"	2"	2"	2"	2"	2"
Flow Rate (Cont. 15 psi) (Peak 25 psi)	38	35	39	47	53	70	66	76	73	84	93
	49	46	50	60	69	91	85	98	94	109	119
Backwash Rate	4.2 gpm	4.2 gpm	5.3 gpm	6.5 gpm	7.5 gpm	10.0 gpm	10.0 gpm	15.0 gpm	15.0 gpm	25.0 gpm	30.0 gpm

SOLD BY:

Products of

